

ZJAZDY

przedmiar

km	str.	szer.	dł.	pow.	rodzaj naw.	promień/skos		podbudowa / koryto	rodzaj pod.	UWAGI	UWAGI	gł. Koryta	obj. Robót ziemnych	
						L	P							
m	L/P	m	m	m2	-	-	-	m2	-					
0+075.00	L	7.00	4.00	31.86	BIT.	R3	R3	4.00	ist / krusz	ist. Naw. Na pow. 27.86 m2		25	1.00	
0+110.00	L	5.00	4.00	23.86	BIT.	R3	R3	23.86	krusz			25	5.97	
0+130.00	L	5.00	4.00	23.86	BIT.	R3	R3	23.86	krusz			25	5.97	
0+186.00	L	5.12	2.40	15.84	BIT.	R3	R3	15.84	krusz			25	3.96	
0+225.00	P	4.00	3.00	28.11	BIT.	R5	R2	28.11	krusz			25	7.03	
0+231.50	L	5.00	3.00	18.86	BIT.	R3	R3	18.86	krusz			25	4.72	
0+282.00	L	7.00	3.00	24.86	KOST.	R3	R3	0.00	IST	PRZE. KOST.	BEZ KOR.	0	0.00	
0+295.00	L	6.00	3.00	21.86	BIT.	R3	R3	21.86	krusz			25	5.47	
0+325.00	P	4.00	3.00	28.11	BIT.	R2	R5	28.11	krusz			25	7.03	
0+377.00	L	5.00	5.00	28.02	BIT.	R3	R2.25	28.02	krusz			25	7.01	
0+386.00	L	4.00	5.00	23.02	BIT.	R2.25	R3	23.02	krusz			25	5.76	
0+397.00	P	4.00	4.00	28.11	BIT.	R2	R5	28.11	krusz			25	7.03	
0+412.00	L	3.50	3.00	14.36	BIT.	R3	R3	14.36	krusz			25	3.59	
0+437.00	P	0.80	3.00	17.36	BIT.	R3	R3	17.36	krusz			25	4.34	
0+440.00	L	4.20	4.00	38.03	BIT.	R3	R3	38.03	krusz			25	9.51	
0+457.00	L	5.00	4.00	23.86	BIT.	R3	R3	23.86	krusz			25	5.97	
0+469.00	P	4.50	3.00	17.36	BIT.	R3	R3	17.36	krusz			25	4.34	
0+558.00	L	5.00	3.00	18.86	BIT.	R3	R3	18.86	krusz			25	4.72	
0+592.00	L	4.00	3.00	15.86	BIT.	R3	R3	15.86	krusz			25	3.97	
0+595.00	P	3.00	3.00	12.86	BIT.	R3	R3	12.86	krusz			25	3.22	
0+609.00	P	3.00	3.00	12.86	BIT.	R3	R3	12.86	krusz			25	3.22	
				467.78					415.06					103.77

POZYCJE KOSZTORYSOWE
ZJAZDY KOSTKA

1	KOSTKA BRUKOWA BETONOWA - PRZEŁOŻENIE ISTNIEJĄCEJ NAW. Z KOSTKI BRUK. BETONOWEJ	24.86	m ²
---	---	-------	----------------

ZJAZDY BITUMICZNE

1	PROFILOWANIE I ZAGĘSZCZENIE PODŁOŻA	415.06	m ²
2	PODBUDOWA KŁSM gr. 20 cm	415.06	m ²
3	W-WA ŚCIERALNA AC11S GR. 5 CM + SKROPIENIE EMULSJĄ ASFALTOWĄ	442.92	m ²